

**COOLEEDGE**

## COOLEEDGE CE COMPLIANT LED DRIVERS - SPECIFICATIONS

PROJECT		REFERENCE TYPE	
SPECIFIED BY		QUANTITY	
DATE		NOTE	For Luminous Surfaces

### INTERIOR DRIVERS

**Purpose:** Cooledge Interior CE Compliant LED Drivers are used to power the following products:

- Cooledge TILE Interior
- Cooledge TILE Tunable White
- Cooledge LINE

### FEATURES

- 58 VDC Constant Voltage output
- 0/1-10V dimming & CCT tuning
- 2-channel driver incorporates deep dimming to 0.05% light output
- 2-channel driver offers flicker-free dimming at 3000Hz

### CERTIFICATIONS



### WARRANTY



5 Year Limited Warranty:  
Parts and workmanship

Category	1-Channel (Dimming)	2-Channel (Dimming + Tuning)
Driver Enclosure Size (mm)	199 x 63 x 35	199 x 63 x 35
Dimming Module ("TWC") Size (mm)	123 x 45 x 24	123 x 45 x 24
Input Frequency (Hz)	50-60	50-60
Nominal Input Voltage Range (VAC)	220-277	220-277
Output Power (W)	90W	90W
Constant Voltage Output (VDC)	58*	58*
Efficiency (%) – typical at full load	91	91
Power Factor – full load	0.95	0.95
Start time at full load (sec) – typical	0.85	0.85
Max Inrush Current	60A	60A
Standard Protection – Overvoltage, Overcurrent, Short Circuit	YES + Overtemperature	YES + Overtemperature
Dimming Control Protocol*	1-10V*	1-10V*
Dimming Range (%)	0.05 - 100	0.05 - 100
Dimming Frequency (Hz)	3000	3000
Maximum Control Current (Source)*	3mA	3mA
# Input Control Conductors (Class 2)	2 (0.33-0.52mm <sup>2</sup> )	4 (0.33-0.52mm <sup>2</sup> )
Ingress Protection Rating	Dry Location	Dry Location
Humidity (%) – max. relative, non-condensing	90	90
Operating Temperature Range (°C)	0 - 50°C	0 - 50°C
Storage Temperature Range (°C)	-40 - +80°C	-40 - +80°C
Rated Lifetime (hr)	70,000	70,000
CE Compliance	EN/IEC 60598 (System) EN/IEC 55015 (Class B) EN/IEC 6157: 2009 EN/IEC 61000-3-2, 3 EN/IEC 61347-1 EN/IEC 61347-2-13 EN/IEC 61000-4-2,3,4,5,6,8,11 (Class A)	EN/IEC 60598 (System) EN/IEC 55015 (Class B) EN/IEC 6157: 2009 EN/IEC 61000-3-2, 3 EN/IEC 61347-1 EN/IEC 61347-2-13 EN/IEC 61000-4-2,3,4,5,6,8,11 (Class A)
RoHS Compliance	Yes	Yes


\*Set at factory

### HOW TO ORDER

PSD	-	090	-	58V	-	010
<b>PRODUCT</b> PSD = Power Supply - Dimmable		<b>POWER</b> 090 = 90W		<b>CHANNELS</b> 1CH = 1 Channel 2CH = 2 Channel		<b>OUTPUT VOLTS</b> 58V
						<b>CONTROL PROTOCOL</b> 010 = 0/1-10V

Example: EPSD-090-1CH-58V-010

Cooledge Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.



**COOLEEDGE**

## COOLEEDGE CE COMPLIANT LED DRIVERS - SPECIFICATIONS

PROJECT		REFERENCE TYPE	
SPECIFIED BY		QUANTITY	
DATE		NOTE	For Luminous Surfaces

### EXTERIOR DRIVERS

**Purpose:** Cooledge Exterior CE Compliant LED Drivers are used to power the following products:

- Cooledge TILE Exterior

### FEATURES

- 24 VDC Constant Voltage output
- IP65 Rated Enclosure Available

### CERTIFICATIONS



### WARRANTY



5 Year Limited Warranty:  
Parts and workmanship

Category	Built-in Installation Type	Independent Mounting Type
Driver Housing Size (mm)	241 x 43 x 30	241 x 43 x 30
Enclosure Size	Not Applicable	356 x 127 x 76
Input Frequency (Hz)	50-60	50-60
Nominal Input Voltage Range (VAC)	120-277	120-277
Output Power (W)	90	90
Constant Voltage Output (VDC)	24	24
Efficiency (%) – typical at full load	89 (240VAC)	89 (240VAC)
Power Factor – typical at full load	0.96 (240VAC)	0.96 (240VAC)
Total Harmonic Distortion (%) – typical at full load	< 15 (240VAC)	< 15 (240VAC)
Max Inrush Current (A) - typical	8 (240VAC)	8 (240VAC)
Standard Protection – Overvoltage, Overcurrent, Short Circuit	Yes + Overtemperature (Auto re-set)	Yes + Overtemperature (Auto re-set)
Ingress Protection Rating	Provided by others per IEC 60634	IP65
Operating Temperature Range (°C)	-40 - +55 (within the enclosure)	-20 - 50°C
Storage Temperature Range (°C)	-40 - 70°C	-40 - 70°C
Maximum Case Temperature - Tc (°C)	85	Not Applicable
Rated Lifetime (hr)	50,000	50,000
CE Compliance	EN/IEC 55015 (Class B) EN/IEC 61547: 2009 EN/IEC 61000-3-2, 3 EN/IEC 61347-1 EN/IEC 61347-2-13 EN/IEC 61000-4-2,3,4,5,6,8,11	EN/IEC 60598 (System) EN/IEC 55015 (Class B) EN/IEC 61547: 2009 EN/IEC 61000-3-2, 3 EN/IEC 61347-1 EN/IEC 61347-2-13 EN/IEC 61000-4-2,3,4,5,6,8,11
RoHS Compliance	Yes	Yes

### HOW TO ORDER

	-	090	-	24V
<u>PRODUCT</u> EPSS = Enclosed Power Supply - Static PSS = Power Supply - Static*		<u>POWER</u> 090 = 90W		<u>OUTPUT VOLTS</u> 24V

Example: PSS-090-24V

\*Consult Cooledge for dimming options

Cooledge Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.