



## COOLEEDGE CUL LISTED LED DRIVERS - SPECIFICATIONS

PROJECT		REFERENCE TYPE	
SPECIFIED BY		QUANTITY	
DATE		NOTE	For Luminous Surfaces

### INTERIOR DRIVERS

**Purpose:** Cooleedge Interior cUL Listed LED Drivers are used to power the following products:

- Cooleedge TILE Interior
- Cooleedge TILE Tunable White
- Cooleedge LINE

### FEATURES

- 58 VDC Constant Voltage output
- 0-10V dimming & CCT tuning
- 2-channel driver incorporates deep dimming to 0.05% light output
- 2-channel driver offers flicker-free dimming at 3000Hz

### CERTIFICATIONS



### WARRANTY



5 Year Limited Warranty:  
Parts and workmanship.

Category	1-Channel (Dimming)	2-Channel (Dimming + Tuning)
Enclosure Size (in)	11 x 4 x 3	11 x 4 x 3
Input Frequency (Hz)	47-63	47-63
Nominal Input Voltage Range (VAC)	120-277	120-277
Output Power (W)	90W	90W
Constant Voltage Output (VDC)	58	58
Efficiency (%) - typical at full load	89% (120V) 92% (277V)	87% (120V) 90% (277V)
Power Factor - full load	0.998	0.998
Total Harmonic Distortion (%) - full load	<10	<10
Start time at full load (sec) - typical	1.0	1.0
Max Inrush Current	NEMA 410-2015	NEMA 410-2015
Max Leakage Current (MIU)	0.5	0.5
Standard Protection - Overvoltage, Overcurrent, Short Circuit	Yes + Overtemperature	Yes
Dimming Control Protocol*	0-10V*	0-10V*
Dimming Range (%)	1-100	0.05-100
Dimming Frequency (Hz)	2000	3000
Maximum Control Current (Source)*	2mA	2mA
# Input Control Conductors (Class 2)	2 (20-22 AWG)	4 (20-22 AWG)
Ingress Protection Rating	Dry location	Dry location
Humidity (%) – max. relative, non-condensing	90	90
Operating Temperature Range (°C/°F)	0 - 40°C 32 - 104°F	0 - 40°C 32 - 104°F
Storage Temperature Range (°C/°F)	20 - 70°C -4 - 158°F	20 - 70°C -4 - 158°F
Rated Lifetime (hr)	70,000	70,000
UL Certification	cUL Listed	cUL Listed
FCC Rating – FCC 47, Part 15	Class A	Class A
ANSI Standards	ANSI/IEEE C62.41 cat A	ANSI/IEEE C62.41 cat A
RoHS Compliance	Yes	Yes


\*Compliant with IEC Standard 60929 Annex E (Ballasts)

### HOW TO ORDER

EP	PSD	-	090	-	58V	-	010
<b>PRODUCT</b>	<b>POWER</b>		<b>CHANNELS</b>		<b>OUTPUT VOLTS</b>	<b>CONTROL PROTOCOL</b>	
EP	PSD = Enclosed Power Supply - Dimmable	090 = 90W	1CH = 1 Channel 2CH = 2 Channel	58V	010 = 0-10V		

Example: EP-PSD-090-1CH-58V-010

Cooleedge Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.



**COOLEEDGE**

## COOLEEDGE CUL LISTED LED DRIVERS - SPECIFICATIONS

PROJECT		REFERENCE TYPE	
SPECIFIED BY		QUANTITY	
DATE		NOTE	For Luminous Surfaces

### EXTERIOR DRIVERS

**Purpose:** Cooledge Exterior cUL Listed LED Drivers are used to power the following products:

- Cooledge TILE Exterior

### FEATURES

- 24 VDC Constant Voltage output
- IP65 Rated Enclosure included

Enclosure Size (in)	14 x 5 x 3
Input Frequency (Hz)	47-63
Nominal Input Voltage Range (VAC)	120-277
Output Power (W)	90W
Constant Voltage Output (VDC)	24
Efficiency (%) - typical at full load	88% (120V)
Power Factor - full load	0.93
Total Harmonic Distortion (%) - full load	<20
Max Inrush Current (A)	12
Ingress Protection Rating (enclosure)	IP65
Standard Protection - Overvoltage, Overcurrent, Short Circuit	Yes + Overtemperature
Rated Lifetime (hr)	50,000
Operating Temperature Range (°C/°F)	-20 - 50°C -4 - 122°F
Storage Temperature Range (°C/°F)	-40 - 70°C -40 - 158°F
UL Certification	cUL Wet Location Listed (UL2108)
FCC Rating – FCC 47, Part 15	Class B
RoHS Compliance	Yes

### CERTIFICATIONS



**RoHS**

### WARRANTY



5 Year Limited Warranty:  
Parts and workmanship .

### HOW TO ORDER

EPSS	-	090	-	24V
<u>PRODUCT</u> EPSS = Enclosed Power Supply - Static*		<u>POWER</u> 090 = 90W		<u>OUTPUT VOLTS</u> 24V

Example: EPSS-090-24V

\*Consult Cooledge for dimming options

Cooledge Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.